

Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1-6 (cancelled)

- Claim 7 (currently amended): ~~The invention according to claim 1A~~ filtering system for filtering working fluid from a machine comprising a filter having a filter media element for filtering said working fluid, said filter having a first inlet receiving working fluid from said machine, said filter having a first outlet returning working fluid to said machine, said filter
- 5 having a second inlet receiving a cleaning fluid from a source of cleaning fluid, said filter having a second outlet exhausting said cleaning fluid, said filter media element having a clean side communicating with said first outlet and said second inlet, said filter media element having a dirty side communicating with said first inlet and said second outlet, said filter having a first flowpath therethrough from said first inlet through said filter media
- 10 element in one direction to said first outlet, said filter having a second flowpath therethrough from said second inlet through said filter media element in the opposite direction to said second outlet, said first and second flowpaths having common but opposite direction portions through said filter media element, said filter having a filtering mode of operation with said second inlet closed and said second outlet closed and filtering fluid flow
- 15 therethrough along said first flowpath, said filter having a backwash mode of operation with said second inlet open and said second outlet open and said cleaning fluid flowing therethrough along said second flowpath and backwashing contaminant-laden working fluid from said dirty side of said filter media element to said second outlet, a contaminant separator having an inlet connected to said second outlet of said filter and receiving and
- 20 separating contaminant from said contaminant-laden working fluid, wherein said contaminant separator comprises a centrifuge having a rotor separating contaminant from working fluid, and a storage container storing said contaminant, wherein said rotor is driven to rotate by a motive force, and wherein said motive force and said cleaning fluid are each provided by pressurized fluid, namely pressurized drive fluid for said motive force, and

Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

- 25 pressurized backflushing fluid for said cleaning fluid, wherein backflushing pressure is applied by pressurized backflushing fluid from said second inlet, and wherein said motive force is applied by pressurized drive fluid externally of said rotor and externally of said storage container.

Claim 8 (original): The invention according to claim 7 wherein said rotor of said centrifuge is driven to rotate by a motive force, and wherein said motive force and said cleaning fluid are each provided by pressurized air.

B1  
Claim 9 (original): The invention according to claim 8 wherein said source of cleaning fluid comprises a source of compressed air, and wherein the same said source of compressed air supplies both said motive force for said rotor and said cleaning fluid for said filter.

Claim 10 (original): The invention according to claim 7 wherein said storage container comprises a second filter media element reducing fluid turbulence particularly during rotor speed gradients at start-up and trapping contaminant particles and reducing particle re-entrainment during said rotor speed gradients.

Claim 11(original): The invention according to claim 10 wherein said second filter media element comprises a matrix of filter material of at least 75% void volume.

Claim 12 (original): The invention according to claim 11 wherein said void volume is at least 95%.

Claim 13 (original): The invention according to claim 7 wherein said centrifuge has a minimum capacity equal to the capacity of said stored contaminant plus the capacity of said filter.

Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

Claim 14 (original): The invention according to claim 13 wherein said rotor includes an annular chamber providing said storage container.

β1  
5 Claim 15 (original): The invention according to claim 7 wherein said rotor of said centrifuge is driven to rotate by a motive force, said motive force and said cleaning fluid are each provided by pressurized air, said source of cleaning fluid comprises a source of compressed air, said source of compressed air supplies both said motive force for said  
10 rotor and said cleaning fluid for said filter, and comprising a first valve controlling the supply of pressurized air from said source of compressed air to said second inlet of said filter, and a second valve controlling the supply of pressurized air from said source of compressed air to said rotor of said centrifuge, said first and second valves operating such that said rotor begins spinning prior to introduction of contaminant-laden working fluid to said inlet of said centrifuge such that the centrifugal force of the already spinning rotor creates a hollow central air core in said contaminant-laden working fluid allowing escape of air.

Claims 16 (currently amended): In a filtering system for filtering working fluid from a machine ~~where filter capacity is too low for a permanent filter yet flow rate is too high for a centrifuge~~, a combination ~~employing the flow rate capability of a filter with the storage capacity capability of a centrifuge~~, comprising a cleanable filter having a filter media  
5 element for filtering said working fluid, said cleanable filter having a first inlet receiving working fluid from said machine, said cleanable filter having a first outlet returning working fluid to said machine, said cleanable filter having a second inlet receiving a cleaning fluid from a source of cleaning fluid, said cleanable filter having a second outlet exhausting said cleaning fluid, said filter media element having a clean side  
10 communicating with said first outlet and said second inlet, said filter media element having a dirty side communicating with said first inlet and said second outlet, said cleanable filter having a first flowpath therethrough from said first inlet through said filter media element in one direction to said first outlet, said cleanable filter having a second

Appl. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

15 flowpath therethrough from said second inlet through said filter media element in the  
opposite direction to said second outlet, said first and second flowpaths having common  
but opposite direction portions through said filter media element, said cleanable filter  
having a filtering mode of operation with said second inlet closed and said second outlet  
closed and filtering fluid flow therethrough along said first flowpath, said cleanable filter  
20 having a backwash mode of operation with said second inlet open and said second outlet  
open and cleaning fluid flowing therethrough along said second flowpath and  
backwashing contaminant-laden working fluid from said dirty side of said filter media  
element to said second outlet, a ~~said~~ centrifuge having an inlet connected to said second  
outlet of said cleanable filter, said centrifuge having a batch processing mode operative  
25 during said backwashing mode of said cleanable filter and receiving said contaminant-  
laden working fluid from said second outlet of said cleanable filter and separating and  
storing contaminant.

β1  
Claim 17 (original): The invention according to claim 16 wherein said cleanable filter is a  
continuous flow filter in said filtering mode, and said centrifuge is a non-continuous flow  
batch processor having a rotor driven during said backwash mode of said cleanable filter  
and separating contaminant, said rotor being nondriven during said filtering mode of said  
5 cleanable filter

Claim 18 (original): The invention according to claim 16 comprising a plurality of said  
cleanable filters having respective said second outlets connected in parallel to said inlet of  
said centrifuge.

Claim 19 (original): The invention according to claim 18 wherein said centrifuge has a  
plurality of batch processing modes operating serially sequentially, one mode for each of  
said cleanable filters.

Claims 20-88 (canceled)

Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

Claim 89 (currently amended): ~~The invention according to claim 88~~ A filtering system for filtering working fluid from a machine, said system combining a cleanable filter and a centrifuge and transferring a contaminant storage function from said cleanable filter to said centrifuge, said cleanable filter having a filter media element for filtering said  
5 working fluid, said cleanable filter having a first inlet receiving working fluid from said machine, said cleanable filter having a first outlet returning working fluid to said machine, said cleanable filter having a second inlet receiving a cleaning fluid from a source of cleaning fluid, said cleanable filter having a second outlet exhausting said cleaning fluid, said filter media element having a clean side communicating with said first  
10 outlet and said second inlet, said filter media element having a dirty side communicating with said first inlet and said second outlet, said cleanable filter having a first flowpath therethrough from said first inlet through said filter media element in one direction to said first outlet, said cleanable filter having a second flowpath therethrough from said second  
15 inlet through said filter media element in the opposite direction to said second outlet, said first and second flowpaths having common but opposite direction portions through said filter media element, said cleanable filter having a filtering mode of operation with said second inlet closed and said second outlet closed and filtering fluid flow therethrough along said first flowpath, said cleanable filter having a backwash mode of operation with  
20 said second inlet open and said second outlet open and cleaning fluid flowing therethrough along said second flowpath and backwashing contaminant-laden working fluid from said dirty side of said filter media element to said second outlet, said centrifuge having an inlet connected to said second outlet of said cleanable filter and receiving contaminant-laden working fluid therefrom and separating and storing contaminant, said centrifuge comprising a housing having a rotor mounted for rotation therein about an axis,  
25 said rotor having an inner cylindrical sidewall with a hollow interior, and an outer cylindrical sidewall spaced radially outwardly of said inner cylindrical sidewall and defining an annular space therebetween, said inner cylindrical sidewall having a transfer passage therethrough providing communication of said hollow interior with said annular

Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

30 space, said housing having an inlet for admitting contaminant-laden fluid to said hollow  
interior of said inner cylindrical sidewall for passing through said transfer passage into  
said annular space for centrifugal separation upon said rotation, said annular space  
providing a storage container storing said contaminant, a standpipe circumscribing said  
inner cylindrical sidewall and dividing said annular space into an inner annular chamber  
35 between said standpipe and said inner cylindrical sidewall, and an outer annular chamber  
between said standpipe and said outer cylindrical sidewall, wherein said rotor has a base  
plate extending between said inner and outer cylindrical sidewalls, said rotor base plate  
has a drain passage communicating with said annular space and effective upon stopping  
of said rotation to drain fluid therefrom, said standpipe has an upper end at said transfer  
passage, and has a lower end at said drain passage, and wherein said contaminant-laden  
40 fluid comprises contaminant-laden liquid in a gas stream, and such that during rotation,  
gas in said gas stream from said transfer passage is vented through said inner annular  
chamber to said drain passage, and contaminant-laden liquid from said transfer passage is  
centrifugally propelled into said outer annular chamber.

B1

Claim 90 (original): The invention according to claim 89 comprising high-loft filter media  
in said outer annular chamber comprising a matrix of filter material of at least 75% void  
volume, said outer annular chamber providing a storage container storing said contaminant  
and retaining said contaminant in said high-loft filter media, said high-loft filter media  
5 retaining and storing said separated contaminant in said outer annular chamber, including  
after said rotation when said rotor is stopped, said high-loft filter media reducing re-  
entrainment of said separated contaminant during start-up at the beginning of the next  
rotation of said rotor.

Claim 91 (original): The invention according to claim 89 wherein said rotor outer cylindrical  
sidewall is removably separable from said base, and wherein said rotor further comprises a  
disposable liner shell capsule extending along and lining the interior of said outer cylindrical  
sidewall and accumulating and containing contaminant, such that said centrifuge may be

Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

- 5 serviced by removing said outer cylindrical sidewall and discarding said disposable liner shell capsule with contained contaminant therein and replacing same with another disposable liner shell capsule.

Claims 92-93 (canceled)

Claim 94 (new): The invention according to claim 7 wherein said backflushing fluid and said working fluid are different fluids.

B1  
Claim 95 (new): The invention according to claim 94 wherein said drive fluid is the same as said backflushing fluid and different than said working fluid.

- Claim 96 (new): The invention according to claim 7 wherein said rotor has an inner cylindrical sidewall, and an outer cylindrical sidewall spaced radially outwardly of said inner cylindrical sidewall, and comprising an annular space between said inner and outer cylindrical sidewalls and providing said storage container, and comprising a turbine on  
5 said outer cylindrical sidewall and external of said annular space for causing rotation of said rotor in response to impingement of said pressurized drive fluid against said turbine.

- Claim 97 (new): The invention according to claim 96 comprising high-loft filter media in said annular space, said high-loft filter media comprising a matrix of filter material of at least 75 % void volume, said matrix of filter material of said high-loft filter media being selected from the group consisting of fibrous material, polyester, foam including  
5 reticulated foam, spun bonded web, wire mesh including stainless steel, and sintered material including porous composites, and wherein said rotor has a base plate extending between said inner and outer cylindrical sidewalls, said rotor base plate having a drain passage communicating with said annular space and effective upon stopping of rotation of said rotor to drain fluid therefrom, said rotor base plate having a configured surface  
10 facing upwardly toward said annular space and having an upper-height outer portion

Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

adjacent said outer cylindrical sidewall, a lower pocket portion, and an intermediate-height inner portion adjacent said inner cylindrical sidewall, said configured surface being tapered radially inwardly and downwardly from said upper-height outer portion to said lower pocket portion and then upwardly to said intermediate-height inner portion, said  
15 upper-height outer portion having a height higher than said intermediate-height inner portion, said intermediate-height inner portion having a height greater than said lower pocket portion, said drain passage being at said intermediate-height inner portion, such that separated contaminant not retained by said high-loft filter media is collected in said lower pocket portion, and fluid above said collected contaminant in said lower pocket  
20 portion drains to said drain passage.

Claim 98 (new): The invention according to claim 89 wherein said standpipe has an upper reach at said upper end at a level vertically below said transfer passage.

Claim 99 (new): The invention according to claim 98 wherein said standpipe has one or more openings at said lower end draining fluid therethrough from said outer annular chamber to said drain passage upon said stopping of said rotation, wherein said rotor has a base plate extending between said inner and outer cylindrical sidewalls, said rotor base  
5 plate has a configured surface facing said annular space and gravitationally guiding drainage of liquid therefrom to said drain passage upon said stopping of rotation, and wherein said standpipe at said lower end is mounted to said rotor base plate at said configured surface, and wherein said configured surface has an upper-height outer portion adjacent said outer cylindrical sidewall, a lower pocket portion, and an intermediate-  
10 height inner portion adjacent said inner cylindrical sidewall, said configured surface being tapered radially inwardly and downwardly from said upper-height outer portion to said lower pocket portion and then upwardly to said intermediate-height inner portion, said upper-height outer portion having a height higher than said intermediate-height inner portion, said intermediate-height inner portion having a height higher than said lower  
15 pocket portion, said drain passage being at said intermediate-height inner portion, such



Appln. No. 09/745,754  
Amendment dated June 4, 2003  
Reply to Office Action of January 24, 2003

131

that separated contaminant is collected in said lower pocket portion, and liquid above said collected contaminant in said lower pocket portion drains to said drain passage.

---